Multilayer Blown Film Plant Models

45-45

50-50

40-40-40

50-50-50

55-55-55

Multilayer Blown Film Plant

Process Material:

LDPE / LLDPE

Application:

For making Multilayer Films for Application in...

Shopping bags, Food packaging, Multilayer Stretch Film, Pouches for Oil, Milk, Ghee etc.

	Sr.	Plant	Screw	Lay Flat	Max. Production	Main	Total Load	Plant Dimensions		
	No.	Model	Size	Width	Capacity(kg/hr)	Motor	Connection(KW)	(Approx.) (Feet)		
			(mm)	(mm)		(H.P.)		L	W	Н
	1	CMBF-45-45	45-45	800	60	15-15	60	25	15	25
	2	CMBF-50-50	50-50	1200	90	25-25	88	30	15	30
	3	CMBF-40-40-40	40-40-40	1000	80	15-15-15	90	35	20	30
	4	CMBF-50-50-50	50-50-50	1200	135	25-25-25	129	45	22	35
	5	CMBF-55-55-55	55-55-55	1500	180	30-30-30	155	45	22	35

Features:

- Availability of different models of Screw diameters ranging from 40 mm to 55 mm
- Production Capacity ranging from 65 kg/hr to 180 kg/hr
- Use of Special Nitro Alloy Steel for Screw & Barrel resulting in long life and trouble free operations
- Helical Gear Box with in-built Heavy duty Thrust Bearings
- Use of Hard Chrome Plated die with Mirror Polishing
- Semi Automatic winding system

• Take-Off Units Equipped with Pneumatic Pressure Control system for easy and smooth operation

Vertical type Rotating Take-Off Unit

Option for Rotating Die Head Available for Two Layer Plant

Plant equipped with....

• Micro Processor based PID Temperature Controllers

All AC Motors with AC Frequency Drives

Our Advantages:

• Highest Production Capacity in the same class of Machinery

Specially designed contol panel for saving up to 10% of Power Consumption Resulting in Optimum Product Costing compared to the Conventional Machinery of the same class



Rotating Die Head



C1/222+224/4, Nr. Hans Chemicals, Phase II, G.I.D.C., Naroda, Ahmedabad – 382330 Phone : +91-9879474145 +91-9377799000

E-mail: sales@cosmicmachines.com

